



# PRASAN INDUSTRIES PRIVATE LIMITED

## BLENDING PLANT OF LUBRICANTS



CIN No. : U23300AS2020PTC020810  
GSTIN : 18AALCP5293J1ZR  
ICE CODE - AALCP5293J

### RIWALOIL 20W40

### PRODUCT DATA SHEET

### GRADES AVAILABLE - RIWALOIL 20W40



#### DESCRIPTION

RIWALOIL 20W40 is blended with structurally modified base stock blended with synergistic additive system for outstanding detergency, dispersancy characteristics, anti- wear and antioxidant properties, high viscosity index and low temperature flow properties. This delicately balanced composition provides and exceeds tough industry performance standards thus ensuring reliability, emission control, economy and endurance.

#### APPLICATION

RIWALOIL 20W40 is recommended for on road high performance 4 Stroke Motor Cycle and Scooters particularly operating with wet clutch system.

#### PERFORMANCE BENEFITS

- ✓ Selected synthetic base stocks impart inherent low temperature pumpability and excellent evaporation control in high speed, high temperature operation.
- ✓ Formulated with highly shear stable viscosity index modifiers which ensure viscosity control over extreme temperatures.
- ✓ Enhanced lubrication to help maintain maximum power and acceleration over the life of the engine.
- ✓ Optimized wet-clutch performance

#### PERFORMANCE STANDARDS

RIWALOIL 20W40 meets the performance requirement of API SM /JASO MA 2 specifications.

#### CHARACTERISTICS

SAE GRADE	20W40
Kinematic Viscosity cSt @ 100C	13.5-15.5
Viscosity Index, Min.	110
Flash point (COC), C Min.	200
Pour Point, C Max	(-) 21
TBN mg KOH/gm	4.5-6.0
Sulphated Ash, % wt	0.61-0.98

#### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Prasan Industries Private Limited, Guwahati, Assam --781001

E-Mail: [info@riwaloil.com](mailto:info@riwaloil.com), Website-[www.riwaloil.com](http://www.riwaloil.com)

