



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

Lubrication oil 15W40

Version 001 Revision Date 07/29/2025 Date of last issue: 11.20.2023
 Date of first issue: 11.20.2023

SECTION 1. IDENTIFICATION

Product name : Lubrication oil 15W40

Manufacturer or supplier's details

Company name of supplier : Prasan Industries Private Limited
 Quality Assurance Dept.

Address : Industrial Estate, Aids Complex,
 Assam, India – 781355

Telephone : +91-7002019033

Emergency telephone : +91-7002019033 (8:00-17:00. IST)

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Substance name : White mineral oil (petroleum)

CAS-No. : 8042-447-5

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|-------------------------------|------------|-----------------------|
| White mineral oil (petroleum) | 8042-447-5 | 100 |

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.





PRASAN INDUSTRIES PRIVATE LIMITED
BLENDING PLANT OF LUBRICANTS

RiwalOil
IMPORTER & EXPORTER

CIN No. : U23300AS2020PTC020610
GSTIN : 18AALCP5293J1ZR
ICE CODE : AALCP5293J

| | |
|---|---|
| | Get medical attention if symptoms occur. |
| In case of skin contact | Wash with water and soap as a precaution Get medical attention if symptoms occur. |
| In case of eye contact | : Flush eyes with water as a precaution. Get medical attention if irritation develops and persists. |
| If swallowed | : If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : None known. |
| Protection of first-aiders | : No special precautions are necessary for first aid responders. |
| Notes to physician | : Treat symptomatically and supportively. |

SECTION 5. FIRE-FIGHTING MEASURES

| | |
|--|---|
| Suitable extinguishing media | : Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical |
| Unsuitable extinguishing media | : None known. |
| Specific hazards during fire fighting | : Exposure to combustion products may be a hazard to health. |
| Hazardous combustion products | : Carbon oxides |
| Specific extinguishing methods | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area. |
| Special protective equipment for fire-fighters | : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|---|--|
| Personal precautions, protective equipment and emergency procedures | : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8). |
|---|--|





PRASAN INDUSTRIES PRIVATE LIMITED
BLENDING PLANT OF LUBRICANTS



CIN No. : U23300AS2020PTC020610
 GSTIN : 18AALCP5293J1ZR
 ICE CODE : AALCP5293J

- Environmental precautions : Avoid release to the environment.
 Prevent further leakage or spillage if safe to do so.
 Prevent spreading over a wide area (e.g., by containment or oil barriers).
 Retain and dispose of contaminated wash water.
 Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
 For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
 Clean up remaining materials from spill with suitable absorbent.
 Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
 Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.


SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
 Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents
 Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-------------------------------|------------|------------------------------------|--|-------|
| White mineral oil (petroleum) | 8042-447-5 | TWA (Inhalable particulate matter) | 5 mg/m ³ | ACGIH |





PRASAN INDUSTRIES PRIVATE LIMITED
BLENDED PLANT OF LUBRICANTS



CIN No. : U23300AS2020PTC020610
 GSTIN : 18AALCP5293J1ZR
 ICE CODE : AALCP5293J

| | | | |
|--|------------|----------------------|-----------|
| | TWA (Mist) | 5 mg/m ³ | OSHA Z-1 |
| | TWA (Mist) | 5 mg/m ³ | NIOSH REL |
| | ST (Mist) | 10 mg/m ³ | NIOSH REL |

Engineering measures : Ensure adequate ventilation, especially in confined areas
 Minimize workplace exposure concentrations

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
 Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
 When using do not eat, drink or smoke.
 Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colorless

Odor : hydrocarbon-like

Odor Threshold : No data available

pH : No data available


Melting point/freezing point : No data available



| | |
|--|--|
| Initial boiling point and boiling range | : > 536 °F / > 280 °C |
| Flash point | : 356 °F / 180 °C |
| Evaporation rate | : No data available |
| Flammability (solid, gas) | : Not applicable |
| Flammability (liquids) | : No data available |
| Upper explosion limit / Upper flammability limit | : 10 %(V) |
| Lower explosion limit / Lower flammability limit | : 1 %(V) |
| Vapor pressure | : < 0.005 Pa (68 °F / 20 °C) |
| Relative vapor density | : No data available |
| Relative density | : 0.850 (59 °F / 15 °C) |
| Density | : 0.850 g/cm ³ (59 °F / 15 °C) |
| Solubility(ies) Water solubility | : slightly soluble |
| Partition coefficient: n-octanol/water | : log Pow: > 6 |
| Autoignition temperature | : > 608 °F / > 320 °C |
| Decomposition temperature | : No data available |
| Viscosity Viscosity, kinematic | : No data available |
| Explosive properties | : Not explosive |
| Oxidizing properties | : The substance or mixture is not classified as oxidizing. |
| Particle size | : Not applicable |

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.





| | |
|------------------------------------|--|
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : Can react with strong oxidizing agents. |
| Conditions to avoid | : None known. |
| Incompatible materials | : Oxidizing agents |
| Hazardous decomposition products | : No hazardous decomposition products are known. |

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

| | |
|---------------------------|---|
| Acute oral toxicity | : LD50 (Rat): > 5,000 mg/kg |
| Acute inhalation toxicity | : LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity |
| Acute dermal toxicity | : LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity |

Skin corrosion/irritation

Not classified based on available information.


Components:

White mineral oil (petroleum):

| | |
|---------|----------------------|
| Species | : Rabbit |
| Result | : No skin irritation |

Serious eye damage/eye irritation

Not classified based on available information.





PRASAN INDUSTRIES PRIVATE LIMITED
BLENDING PLANT OF LUBRICANTS



CIN No. : U23300AS2020PTC020610
GSTIN : 18AALCP5293J12R
ICE CODE : AALCP5293J

Components:

White mineral oil (petroleum):

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

White mineral oil (petroleum):

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cyto-genetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Species : Rat
Application Route : Ingestion
Exposure time : 24 Months
Result : negative

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.





PRASAN INDUSTRIES PRIVATE LIMITED
BLENDED PLANT OF LUBRICANTS

RiwalOil
IMPORTER & EXPORTER

CIN No. : U23300AS2020PTC020610
GSTIN : 18AALCP5293J17R
ICE CODE : AALCP5293J

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Skin contact
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

White mineral oil (petroleum):

Species : Rat
LOAEL : 160 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
LOAEL : >= 1 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 4 Weeks
Method : OECD Test Guideline 412

Aspiration toxicity

Not classified based on available information.





SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

White mineral oil (petroleum):

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l
Exposure time: 28 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1,000 mg/l
Exposure time: 21 d

Persistence and degradability

Components:

White mineral oil (petroleum):

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.
- Contaminated packaging : Empty containers should be taken to an approved waste



PRASAN INDUSTRIES PRIVATE LIMITED
BLENDING PLANT OF LUBRICANTS

RiwalOil
IMPORTER & EXPORTER

CIN No. : U23300AS2020PTC020610
GSTIN : 18AALCP5293J1ZR
ICE CODE : AALCP5293J

handling site for recycling or disposal.
If not otherwise specified. Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards


SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.



SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

| | | |
|------------------------|---|---|
| HEALTH | / | 0 |
| FLAMMABILITY | | 1 |
| PHYSICAL HAZARD | | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "/" represents a chronic hazard, while the "0" represents the absence of a chronic hazard.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- ACGIH / TWA : 8-hour, time-weighted average
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
- OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECL - Korea Existing Chemi-





PRASAN INDUSTRIES PRIVATE LIMITED
BLENDED PLANT OF LUBRICANTS



CIN No : U23300AS2020PTC020610
GSTIN 18AALCP5293J1ZR
ICE CODE AALCP5293J

icals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 07/29/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8

